

The terminal blocks tabulated below have optional single-phase short circuit current ratings. The Terminal Blocks must be protected by the max ampere and Class of overcurrent protective device noted below.

Cat. No.	Wire Range kcmil/AWG Line Load	Overcurrent Protection Fuse Required Class/Max Amp Rating						Torque Nm	SCCR, RMS Sym A (single phase only)	Volts Max ac
		J	T	RK1	RK5	G	CC			
ZS4	14 - 12 STR	50	50	-	-	50	30	0.5 - 0.7	100000	600
ZS6	14 - 10 STR	110	110	100	30	60	30	0.7 - 1.0	100000	600
ZS10	14 - 6 STR	110	110	100	30	60	30	1.0 - 1.6	100000	600
ZS16	14 - 4 STR	150	150	100	30	60	30	1.6 - 2.4	100000	600
ZS35	10 - 1/0 STR	250	250	200	100	60	30	2.8 - 3.0	100000	600
ZS70	4 - 2/0 STR	250	250	200	100	60	30	6.0 - 7.0	100000	600
ZS95	2 - 4/0 STR	350	350	200	100	60	30	9.0 - 9.5	100000	600
ZS4-D2	14 - 12 STR	50	50	-	-	50	30	0.5 - 0.7	100000	600
ZS6-D2	14 - 10 STR	110	110	100	30	60	30	0.7 - 1.0	100000	600

For SCCR ratings, enclosure size employed for tests is 80 x 130 x 100 mm for Cat. Nos. ZS4, ZS6, ZS10, ZS16 and ZS35 and 80 x 130 x 125 mm for Cat. Nos. ZS70, ZS95, ZS4-D2 and ZS6-D2.